



| BACK OF ARRAY HEIGHT (INCHES) | | |
|-------------------------------|----------|----------|
| ANGLE | 'A' MAX. | 'A' MIN. |
| 15 | 93 | 67 |
| 18 | 98 | 72 |
| 21 | 103 | 77 |
| 25 | 110 | 84 |
| 30 | 119 | 93 |
| 35 | 127 | 101 |
| 45 | 141 | 115 |

STAMP & SIGNATURE:
ENGINEERED POWER SOLUTIONS
1405 Spring Street, Suite 204
Paso Robles, CA 93446



PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED HEREIN IS THE SOLE PROPERTY OF NUANCE ENERGY GROUP, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT WRITTEN PERMISSION IS PROHIBITED. (C) COPYRIGHT 2013.

MACHINED FILLET RADII 0.38-1.27 [.015-.050].
BREAK ALL SHARP EDGES 0.2-0.8 [.01-.03] RADII
OR 45°. SURFACE FINISH IN MICRO (P) INCHES
(Ra). INTERPRET DRAWING PER ASME Y14.5,
ASME Y14.36, AND AWS A2.4 STANDARDS.

| | | | |
|----------------------------|-------------------|---|---------------------------------|
| DRAW: RODOLFO PEREIRA | 26/03/2020 | OSPREY POWERPLATFORM | |
| APPROVED: LUKE ASHWORTH | 26/03/2020 | | |
| WEIGHT: N/A lb | | TITLE OSP 2x5 HD 60 CELL 4L ASSEMBLY - SIX LEG | |
| GENERAL TOLERANCES: | | MATERIAL: N/A | |
| DECIMALS .X ± .1 | ANGULAR ∠ ± 1° | SIZE D | DWG NO OSP 2x5 HD 60C 4L ASY |
| .XX ± .01 | | SCALE 1:20 | REV 02 |
| .XXX ± .005 | | | SHEET 1 OF 1 |

FOR STRUCTURAL ELEMENTS ONLY