



BACK OF ARRAY HEIGHT (INCHES)		
ANGLE	'A' MAX.	'A' MIN.
15	98	72
18	105	79
21	111	85
25	120	94
30	130	104
35	140	114
45	158	132

STAMP & SIGNATURE:

ENGINEERED POWER SOLUTIONS
1405 Spring Street, Suite 204
Paso Robles, CA 93446

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED HEREIN IS THE SOLE PROPERTY OF NUANCE ENERGY GROUP, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT WRITTEN PERMISSION IS PROHIBITED. (C) COPYRIGHT 2013.

MACHINED FILLET RADII 0.38-1.27 [.015-.050].
BREAK ALL SHARP EDGES 0.2-0.8 [.01-.03] RADII
OR 45°. SURFACE FINISH IN MICRO (P) INCHES
(Ra). INTERPRET DRAWING PER ASME Y14.5,
ASME Y14.36, AND AWS A2.4 STANDARDS.

DRAW: RODOLFO PEREIRA 26/03/2020

APPROVED: LUKE ASHWORTH 26/03/2020

WEIGHT: N/A lb

GENERAL TOLERANCES:

DECIMALS	ANGULAR
.X ± .1	
.XX ± .01	≤ ± 1°
.XXX ± .005	

TITLE: OSPREY POWERPLATFORM

OSP 2x5 XHD 72 CELL 4L ASSEMBLY - SIX LEG

MATERIAL: N/A

SIZE: D	DWG NO: OSP 2x5 XHD 72C 4L ASY	REV: 02
SCALE: 1:20	SHEET 1 OF 1	

FOR STRUCTURAL ELEMENTS ONLY