



| BACK OF ARRAY HEIGHT (INCHES) | | |
|-------------------------------|----------|----------|
| ANGLE | 'A' MAX. | 'A' MIN. |
| 15 | 93 | 67 |
| 18 | 98 | 72 |
| 21 | 103 | 77 |
| 25 | 110 | 84 |
| 30 | 119 | 93 |
| 35 | 127 | 101 |
| 45 | 141 | 115 |

STAMP & SIGNATURE:
ENGINEERED POWER SOLUTIONS
 1405 Spring Street, Suite 204
 Paso Robles, CA 93446



PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED HEREIN IS THE SOLE PROPERTY OF NUANCE ENERGY GROUP, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT WRITTEN PERMISSION IS PROHIBITED. (C) COPYRIGHT 2013.

MACHINED FILLET RADII 0.38-1.27 [.015-.050]. BREAK ALL SHARP EDGES 0.2-0.8 [.01-.03] RADII OR 45°. SURFACE FINISH IN MICRO (P) INCHES (Ra). INTERPRET DRAWING PER ASME Y14.5, ASME Y14.36, AND AWS A2.4 STANDARDS.

DRAWN: RODOLFO PEREIRA 27/03/2020
 APPROVED: LUKE ASHWORTH 27/03/2020
 WEIGHT: N/A lb
 GENERAL TOLERANCES:
 DECIMALS .X ± .1
 .XX ± .01
 .XXX ± .005

OSPREY POWERPLATFORM
 TITLE: OSP 2x6 XHD 60 CELL 6L ASSEMBLY - SIX LEG
 MATERIAL: N/A
 SIZE: D
 DWG NO: OSP 2x6 XHD 60C 6L ASY
 REV: 02
 SCALE: 1:20
 SHEET 1 OF 1

FOR STRUCTURAL ELEMENTS ONLY