



BACK OF ARRAY HEIGHT (INCHES)		
ANGLE	'A' MAX.	'A' MIN.
15	93	67
18	98	72
21	103	77
25	110	84
30	119	93
35	127	101
45	141	115

STAMP & SIGNATURE:  
**ENGINEERED POWER SOLUTIONS**  
 1405 Spring Street, Suite 204  
 Paso Robles, CA 93446



PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED HERE IN IS THE SOLE PROPERTY OF NUANCE ENERGY GROUP, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT WRITTEN PERMISSION IS PROHIBITED. (C) COPYRIGHT 2013. ALL RIGHTS RESERVED.

MACHINED FILLET RADII 0.38-1.27 [.015-.050]. BREAK ALL SHARP EDGES 0.2-0.8 [.01-.03] RADII OR 45°. SURFACE FINISH IN MICRO (P) INCHES (Ra). INTERPRET DRAWING PER ASME Y14.5, ASME Y14.36, AND AWS A2.4 STANDARDS.

DRAW:  
 RODOLFO PEREIRA 26/03/2020  
 APPROVED:  
 LUKE ASHWORTH 26/03/2020  
 WEIGHT:  
 N/A lb  
 GENERAL TOLERANCES:  
 DECIMALS .X ± .1  
 .XX ± .01  
 .XXX ± .005  
 ANGULAR  
 <math>\leq \pm 1^\circ</math>

**OSPREY POWERPLATFORM**  
 TITLE  
**OSP 2x8 HD 60 CELL 6L ASSEMBLY - SIX LEG**  
 MATERIAL: N/A  
 SIZE  
 D  
 DWG NO  
 OSP 2x8 HD 60C 6L ASY  
 REV  
 02  
 SCALE 1:20  
 SHEET 1 OF 1

FOR STRUCTURAL ELEMENTS ONLY