



| BACK OF ARRAY HEIGHT (INCHES) |          |          |
|-------------------------------|----------|----------|
| ANGLE                         | 'A' MAX. | 'A' MIN. |
| 15                            | 93       | 67       |
| 18                            | 98       | 72       |
| 21                            | 103      | 77       |
| 25                            | 110      | 84       |
| 30                            | 119      | 93       |
| 35                            | 127      | 101      |
| 45                            | 141      | 115      |

STAMP & SIGNATURE:  
**ENGINEERED POWER SOLUTIONS**  
 1405 Spring Street, Suite 204  
 Paso Robles, CA 93446



PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED HEREIN IS THE SOLE PROPERTY OF NUANCE ENERGY GROUP, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT WRITTEN PERMISSION IS PROHIBITED. (C) COPYRIGHT 2013.  
 MACHINED FILLET RADII 0.38-1.27 [.015-.050]. BREAK ALL SHARP EDGES 0.2-0.8 [.01-.03] RADII OR 45°. SURFACE FINISH IN MICRO (P) INCHES (Ra). INTERPRET DRAWING PER ASME Y14.5, ASME Y14.36, AND AWS A2.4 STANDARDS.

|                            |                   |   |   |
|----------------------------|-------------------|---|---|
| DRAW:<br>RODOLFO PEREIRA   | 27/03/2020        | <b>OSPREY POWERPLATFORM</b>                               |   |
| APPROVED:<br>LUKE ASHWORTH | 27/03/2020        | TITLE<br><b>OSP 2x8 STD 60 CELL 6L ASSEMBLY - SIX LEG</b> |   |
| WEIGHT:<br>N/A lb          |                   | MATERIAL: N/A   |   |
| GENERAL TOLERANCES:        |                   | SIZE<br><b>D</b>  | DWG NO<br><b>OSP 2x8 STD 60C 6L ASY</b> |
| DECIMALS<br>.X ± .1        | ANGULAR<br>∠ ± 1° | SCALE<br>1:20   | REV<br>02                               |
| .XX ± .01                  |                   |   |   |
| .XXX ± .005                |                   |   |   |

FOR STRUCTURAL ELEMENTS ONLY