



BACK OF ARRAY HEIGHT (INCHES)		
ANGLE	'A' MAX.	'A' MIN.
15	98	72
18	105	79
21	111	85
25	120	94
30	130	104
35	140	114
45	158	132

STAMP & SIGNATURE:  
**ENGINEERED POWER SOLUTIONS**  
 1405 Spring Street, Suite 204  
 Paso Robles, CA 93446



PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED HEREIN IS THE SOLE PROPERTY OF NUANCE ENERGY GROUP, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT WRITTEN PERMISSION IS PROHIBITED. (C) COPYRIGHT 2013.  
 MACHINED FILLET RADII 0.38-1.27 [.015-.050]. BREAK ALL SHARP EDGES 0.2-0.8 [.01-.03] RADII OR 45°. SURFACE FINISH IN MICRO (P) INCHES (Ra). INTERPRET DRAWING PER ASME Y14.5, ASME Y14.36, AND AWS A2.4 STANDARDS.

DRAW: RODOLFO PEREIRA	26/03/2020	<b>OSPREY POWERPLATFORM</b>	
APPROVED: LUKE ASHWORTH	26/03/2020		
WEIGHT: N/A lb		TITLE <b>OSP 2x8 XHD 72 CELL 6L ASSEMBLY - SIX LEG</b>	
GENERAL TOLERANCES:		MATERIAL: N/A	
DECIMALS .X ± .1	ANGULAR ∠ ± 1°	SIZE <b>D</b>	DWG NO <b>OSP 2x8 XHD 72C 6L ASY</b>
.XX ± .01		SCALE 1:20	REV 02
.XXX ± .005			SHEET 1 OF 1

FOR STRUCTURAL ELEMENTS ONLY