



Osprey PowerRack Capacity

	4x3-2 MAX	4x3-2 LTE	4x3-3 MAX	4x3-3 LTE	4x4-2 MAX	4x4-2 LTE	4x4-3 MAX	4x4-3 LTE	4x5-3 MAX	4x5-3 LTE	4x5-4 MAX	4x5-4 LTE	4x6-4 MAX	4x6-4 LTE	
10 Degree	70	1	1	1	1	1	1	1	1	1	1	1	1	1	
	80	1	1	1	1	1	1	1	1	1	1	1	1	1	
	90	1	1		1	1	1	1	1	1		1	1	1	
	100	1	1		1	1	1	1	1	1		1	1	1	
	110	1	1		1	2	1	1	1	2	1		1	2	1
	120	2	1		1			1	1	2	2		1	2	2
	130	2	2		1			2	1	2	2		2		2
	140	2	2					2	2	3	2				2
15 Degree	70	1	1	1	1	1	1	1	1	1	1	1	1	1	
	80	1	1	1	1	1	1	1	1	1	1	1	1	1	
	90	1	1		1	1	1	1	1	1		1	1	1	
	100	1	1		1	2	1	1	1	2	1		1	2	1
	110	2	1		1	2	2	1	1	2	2		1	2	2
	120	2	2		1			2	1	2	2		2	2	2
	130	2	2		2			2	2	3	2		2		2
	140	2	2					2	2	3	3				3
18 Degree	70	1	1	1	1	1	1	1	1	1	1	1	1	1	
	80	1	1	1	1	1	1	1	1	1	1	1	1	1	
	90	1	1		1	1	1	1	1	1		1	1	1	
	100	1	1		1	2	2	1	1	2	1		1	2	1
	110	2	1		1	2	2	1	1	2	2		1	2	2
	120	2	2		1			2	1	2	2		2	2	2
	130	2	2		2			2	2	3	2		2		2
	140	3	2					2	2	3	3				3
20 Degree	70	1	1	1	1	1	1	1	1	1	1	1	1	1	
	80	1	1	1	1	1	1	1	1	1	1	1	1	1	
	90	1	1		1	1	1	1	1	1		1	1	1	
	100	1	1		1	2	2	1	1	2	1		1	2	1
	110	2	1		1	2	2	2	1	2	2		1	2	2
	120	2	1		1			2	1	2	2		2	3	2
	130	2	2		2			2	2	3	2		2		2
	140	3	2					2	2	3	3				3
25 Degree	70	1	1	1	1	1	1	1	1	1	1	1	1	1	
	80	1	1	1	1	1	1	1	1	1	1	1	1	1	
	90	1	1	1	1	2	2	1	1	2	1	2	1	2	1
	100	2	1	1	1	2	2	1	1	2	2	2	1	2	2
	110	2	2	2	2			2	2				2		2
	120			2	2			2	2				2		
	130				2				2						
	140								2						
30 Degree	70	1	1	1	1	1	1	1	1	1	1	1	1	1	
	80	1	1	1	1	2	1	1	1	1	1	1	1	1	
	90	1	1	1	1	2	2	1	1	2	2	2	1	2	2
	100	2	2	2	1	2	2	2	1	2	2	2	2	2	2
	110	2	2	2	2			2	2				2		2
	120			2	2			2	2				2		
	130				2				2						
	140														
35 Degree	70	1	1	1	1	1	1	1	1	1	1	1	1	1	
	80	1	1	1	1	2	1	1	1	1	1	1	1	1	
	90	1	1	1	1	2	2	1	1	2	2	2	1	2	1
	100	2	2	1	1	2	2	1	1	2	2	2	2	2	2
	110	2	2	2	2			2	2				2		2
	120			2	2			2	2				2		
	130				2				2						
	140								2						

The OPR Max and LTE are for panel dimensions up to 95x45" and 85-40" respectively.

Numbers in black refer to systems up to 30PSF, White numbers up to 60PSF

Some arrangements will require up to 3 anchors on the rear legs based on loading, consult with a Nuance representative for details.